

## TAMADA CORPORATION FAX:+01(U)-/U-ZU/-U-1U

TEL:+81(0)-76-267-4888 FAX:+81(0)-76-267-5415

#### Why SF Double Tank

#### Reputation

We bring our 71-year history of innovation and reliability to oil and water tank installations.



With 13 branches, 3 factories in all over Japan and 1 factory in Hai Phong Vietnam.




Pollution





Single Wall Tank will rust after long time buried underground without any signal.

Only for moving the corroded tank will cost more than 2millions Yen and does not include any environmental remediation costs.



<sup>\*</sup> Fig2 Effects of Oil Spills https://greenliving.lovetoknow.com/Effects\_of\_Oil\_Spills(2021/9/7)

<sup>\*</sup> Fig3 Buncefield fire 15 years on: The Hertfordshire explosion that was heard in Holland and seen from space https://www.hertfordshiremercury.co.uk/news/hertfordshirenews/buncefield-fire-hertfordshire-explosion-heard-

#### **TOP Share in Japan**



SF Double Wall Tank

Spray up method

#### **Feature**


# Excellent in Economy, Safety and Quality

The SF Double-Wall Tank which means a tank with Double Wall S and F. S stands for Steel, F stands for FRP(Fiber Reinforcement Plastic) non-corrosive nature. Between the Steel layer and FRP layer there is a gap which helps the tank to monitor leakage with float sensor equipped in the tank. We call the gap as interstice. The FRP layer is formed by advanced Spray-up technology and hand layup method for special parts helps to make seamless secondary FRP tank.

Hand lay up method







secondary tank

### MAINSTREAM BUSINESS



